Interprogram Messaging Manager

Contents

About the IPM Manager 7-3
About AOCE Interprogram Messages 7-4
Message Queues 7-8
Addresses 7-9
Report Messages 7-9
Addressing IPM Messages 7-10
Direct Addressing 7-11
AppleTalk Direct Addressing 7-12
Telephone Direct Addressing 7-12
Indirect Addressing 7-14
Attribute-Type Indirect Addressing 7-15
Queue-Name Format for Attribute Values 7-16
Using the IPM Manager 7-17
Determining Whether the Collaboration Toolbox is Available 7-17
Determining the Version of the Collaboration Toolbox 7-17
Error Handling 7-18
Creating a Message 7-18
Initiating the Message-Creation Process 7-18
Adding Information to the Message 7-19
Ending a Message 7-20
Creating and Managing Message Queues 7-20
Creating and Opening a Queue 7-20
Specifying a Queue Filter and Enumerating a Queue 7-21
Closing a Queue 7-22
Reading Messages 7-22
IPM Manager Reference 7-24
Data Types 7-24

Message Addressing Structures 7-24
Message and Block Types 7-26
Delivery Notification 7-28
Filter Structures 7-34
Message Information Structure 7-36
Header Information Structures 7-37
Sender Structure 7-39
Interprogram Messaging Parameter Block Header 7-40
Asynchronous or Synchronous Operations 7-41
Completion Routines and Polling Options 7-41
IPM Manager Functions 7-42
Calling an IPM Function From Assembly Language 7-43
Creating a New Message 7-43
Managing Message Queues 7-68
Listing and Reading Messages 7-80
Deleting Messages 7-105
Utility Functions 7-107
Application-Defined Functions 7-114
Summary of the IPM Manager 7-117
C Summary 7-117
Constants and Data Types 7-117
IPM Manager Functions 7-133
Pascal Summary 7-135
Constants 7-135
Data Types 7-138
IPM Manager Functions 7-153
Assembly-Language Summary 7-156
Result Codes 7-157